



Brief paper

Certification of the proximal gradient method under fixed-point arithmetic for box-constrained QP problems[☆]

Pablo Krupa^{a,*}, Omar Inverso^b, Mirco Tribastone^c, Alberto Bemporad^c

^a Systems Engineering and Automation Department, Universidad de Sevilla, Seville, Spain

^b Gran Sasso Science Institute (GSSI), L'Aquila, Italy

^c IMT School for Advanced Studies, Lucca, Italy

ARTICLE INFO

Article history:

Received 31 March 2023

Received in revised form 5 July 2023

Accepted 8 September 2023

Available online 11 November 2023

Keywords:

Convex optimization

Embedded systems

Predictive control

Fixed-point arithmetic

Gradient method

Certification

ABSTRACT

In safety-critical applications that rely on the solution of an optimization problem, the certification of the optimization algorithm is of vital importance. Certification and suboptimality results are available for a wide range of optimization algorithms. However, a typical underlying assumption is that the operations performed by the algorithm are exact, i.e., that there is no numerical error during the mathematical operations, which is hardly a valid assumption in a real hardware implementation. This is particularly true in the case of fixed-point hardware, where computational inaccuracies are not uncommon. This article presents a certification procedure for the proximal gradient method for box-constrained QP problems implemented in fixed-point arithmetic. The procedure provides a method to select the minimal fractional precision required to obtain a certain suboptimality bound, indicating the maximum number of iterations of the optimization method required to obtain it. The procedure makes use of formal verification methods to provide arbitrarily tight bounds on the suboptimality guarantee. We apply the proposed certification procedure on the implementation of a non-trivial model predictive controller on 32-bit fixed-point hardware.

© 2023 Elsevier Ltd. All rights reserved.

1. Introduction

Quadratic programming (QP) problems arise in various areas of systems engineering and control, such as model predictive control (MPC), see [Rawlings et al. \(2017\)](#), or reference governors, see [Garone et al. \(2017\)](#), to name a few. Various practical control-related applications, such as the ones listed above, require solving parameter-dependent QP problems at regular intervals on embedded hardware, which poses a challenge due to computational and memory limitations. In recent years there has been a significant advance in this area due to the proposal of efficient QP solvers, some of them for generic QP problems, such as the

OSQP solver presented in [Stellato et al. \(2020\)](#), and some tailored to specific problems, such as the solvers proposed in [Frison and Diehl \(2020\)](#) and [Krupa, Limon et al. \(2021\)](#), which address MPC optimization problems.

In many practical applications of MPC, such as safety-critical systems and space applications, the certification of the maximum number of iterations required by the optimization algorithm and a guarantee of the suboptimality of its provided solution are mandatory for real deployment. Most solvers are based on optimization algorithms with well-known convergence and suboptimality guarantees. The issue is that these guarantees are typically derived considering ideal conditions, e.g., under the assumption that the mathematical operations performed by the algorithm are error-free; an assumption, however, that is no longer valid when the optimization algorithm is implemented on hardware. This is particularly noticeable on fixed-point hardware, where quantization and round-off errors may lead to significant differences with respect to the “exact” counterpart. The magnitude of this difference depends on the number of fractional bits, which must be selected large enough to provide the required guarantees.

In linear-time-invariant (LTI) MPC, the use of *explicit* MPC ([Bemporad, 2021](#)) instead of an iterative solver provides a direct certification of the computation time. However, explicit MPC may require a considerable amount of memory to implement and is only applicable to LTI systems ([Bemporad, 2021](#)).

[☆] This work was supported in part by Grant Margarita Salas, funded by the Ministerio de Universidades and the European Union (NextGenerationEU), by PRO3 MUR project Software Quality, and by PNRR MUR project VITALITY (ECS00000041), Spoke 2 ASTRA - Advanced Space Technologies and Research Alliance. The authors acknowledge the support of the MUR (Italy) Department of Excellence 2023–2027 for GSSI. The material in this paper was not presented at any conference. This paper was recommended for publication in revised form by Associate Editor Martin Monnigmann under the direction of Editor Ian R. Petersen.

* Corresponding author.

E-mail addresses: pkrupa@us.es (P. Krupa), omar.inverso@gssi.it (O. Inverso), mirco.tribastone@imtlucca.it (M. Tribastone), alberto.bemporad@imtlucca.it (A. Bemporad).

In [Patrinos et al. \(2015\)](#), the authors present a dual gradient-projection algorithm for MPC tailored to fixed-point arithmetics. The authors present convergence guarantees and concrete guidelines for selecting the fractional precision to obtain the required suboptimality tolerance. The analysis is done using the notion of the *inexact oracle* from [Devolder et al. \(2014\)](#), which presents a generic framework for analyzing first-order optimization algorithms in which the oracle provides inexact information. This framework can be used to derive convergence rates when inexact gradient information is available by considering the maximum error when computing the gradient. It has, however, two downsides when applied to fixed-point arithmetic. The first is that it only considers errors in the gradient information, i.e., it considers the other operations performed by the algorithm to be exact, which may not always be the case in fixed-point precision. Second, the convergence results are presented in terms of the average of the iterates of the algorithm (instead of with respect to the current iterate), whose value is not generally available in fixed-point arithmetic, since its computation requires dividing by the current number of iterations.

Another approach for analyzing the error propagation is to use *affine arithmetic* ([Fang et al., 2003](#); [Vakili et al., 2013](#)). This framework provides less conservative error bounds than simply considering the worst-case error due to how it handles error propagation in affine operations (addition, subtraction and multiplication by a constant), although the error bounds are still conservative in the presence of multiplications between variables. The bounds can be improved by taking a probabilistic approach, as proposed in [Fang et al. \(2003\)](#), at the expense of no longer having a guaranteed certification. This framework was used in [Nadales et al. \(2022\)](#) to certify the minimum number of fractional bits required to satisfy the desired error bound when performing Lipschitz interpolation for data-driven learning-based control. In this case a tight certification could be proposed due to the simplicity of the algorithm, which only required affine operations. However, its application to iterative convex optimization algorithms would provide conservative results, due, precisely, to their iterative nature along with the presence of multiplications.

Finally, formal verification methods have been used, for example, to synthesize Lyapunov functions ([Ahmed et al., 2020](#)) or to certify the Ellipsoid method ([Cohen et al., 2020](#)), including floating-point arithmetic considerations. [Simić et al. \(2022\)](#) proposed a non-conservative formal verification approach for analyzing error propagation in fixed-point arithmetic. The technique allows to check arbitrarily tight error bounds via a bit-vector encoding into integer arithmetics and then into propositional satisfiability, which allows to use mature SAT-based technology. The authors use their procedure to calculate accurate error bounds on a first-order optimization algorithm up to a given number of iterations. However, due to the bit-precise encoding the computational cost of the analysis becomes prohibitive after only a few iterations, even for small optimization problems; this is an issue since first-order methods may require a significant number of iterations to converge.

In this article we analyze the implementation of the proximal gradient method (PGM) ([Parikh & Boyd, 2013](#)) under fixed-point arithmetic applied to strongly convex QP problems with box constraints; a choice motivated by its simplicity but practical relevance and by its linear convergence guarantees under exact arithmetic. We provide convergence guarantees in terms of the maximum number of iterations of the algorithm as well as suboptimality guarantees of its output. Our certificate is based on the formal verification procedure presented in [Simić et al. \(2022\)](#), which we use to derive arbitrarily tight bounds on the quantities that determine the convergence and suboptimality guarantees. The proposed approach provides a procedure for selecting the

minimum fractional precision required to guarantee the given suboptimality and computation-time specifications. Notably, the important difference with respect to [Simić et al. \(2022\)](#) is that the verification only needs to analyze a single iteration of the PGM, thus remaining tractable for a wider range of problems. The main features of our approach are:

- (i) The suboptimality guarantees are provided in terms of the output of the algorithm, instead of for the averaged iterates used in [Patrinos et al. \(2015\)](#).
- (ii) The bounds that determine the suboptimality guarantees are obtained using the formal verification procedure from [Simić et al. \(2022\)](#), which allows us to provide a non-conservative error-bound of the gradient computation, in that the exact maximum error committed in the computation of the gradient can be approximated to an arbitrarily large precision.
- (iii) The certification results are formal guarantees, instead of the probabilistic ones that would be obtained using probabilistic *affine arithmetic* ([Fang et al., 2003](#)) or Monte Carlo analysis ([Saracco et al., 2012](#)).

We present the application of our approach on a non-trivial MPC problem implemented using 32-bit fixed-point arithmetic.

Notation: Given two vectors $x, y \in \mathbb{R}^n$, $x \leq (\geq) y$ denotes componentwise inequalities and $\langle x, y \rangle$ is their standard inner product. The standard Euclidean norm of a vector $x \in \mathbb{R}^n$ is denoted by $\|x\| \doteq \sqrt{\langle x, x \rangle}$. The closed ball of radius $r \geq 0$ in $\mathbb{R}^n$ is defined as the set $\mathcal{B}_r^n \doteq \{x \in \mathbb{R}^n : \|x\| \leq r\}$. The indicator function of a set $\mathcal{C}$ is denoted by $\mathcal{I}_{\mathcal{C}}$, i.e., $\mathcal{I}_{\mathcal{C}}(x) = 0$ if $x \in \mathcal{C}$ and $\mathcal{I}_{\mathcal{C}}(x) = \infty$ if $x \notin \mathcal{C}$. The subdifferential of a function f is denoted by ∂f . We denote by $\mathbb{R}^+$ the set of strictly positive real numbers. We denote by $\mathbb{R}_{(p,q)}^n \subset \mathbb{R}^n$ the set of vectors whose integer and fractional parts are representable using p and q binary digits, respectively. This notion readily extends to the space of matrices $\mathbb{R}^{n \times m}$, where $\mathbb{R}_{(p,q)}^{n \times m} \subset \mathbb{R}^{n \times m}$ represents the space of matrices whose every element is representable in $\mathbb{R}_{(p,q)}$. For any set $\mathcal{C} \subseteq \mathbb{R}^n$, we denote $\mathcal{C}_{(p,q)} = \{x \in \mathbb{R}_{(p,q)}^n : x \in \mathcal{C}\}$. It is obvious that $x \in \mathcal{C}_{(p,q)} \implies x \in \mathcal{C}$, but not vice-versa. It is also easy to see that $\mathcal{C}_{(p',q')} \subseteq \mathcal{C}_{(p,q)}$ for any $p \geq p'$ and $q \geq q'$, and therefore that $x \in \mathcal{C}_{(p',q')} \implies x \in \mathcal{C}_{(p,q)}$.

2. Exact proximal gradient method

We consider the class of strongly-convex QP problems

$$\begin{aligned} \min_{x \in \mathbb{R}^n} \quad & \frac{1}{2} x^\top Q x + c^\top x \\ \text{s.t.} \quad & \ell \leq x \leq u, \end{aligned} \quad (\mathcal{P})$$

where $c, \ell, u, \in \mathbb{R}_{(p',q')}^n$, with $\ell \leq u$, and $Q \in \mathbb{R}_{(p',q')}^{n \times n}$, for some finite positive p' and q' . In this article we are interested in finding a suboptimal solution of problem $(\mathcal{P})$, using the proximal gradient method (PGM) ([Parikh & Boyd, 2013](#)), for any given realization of the ingredients of problem $(\mathcal{P})$ satisfying

$$Q \in \mathcal{Q} \subset \mathbb{R}_{(p',q')}^{n \times n}, \quad c \in \{c \in \mathbb{R}_{(p',q')}^n : c_{\min} \leq c \leq c_{\max}\}, \quad (1a)$$

$$\ell \in \{\ell \in \mathbb{R}_{(p',q')}^n : \ell_{\min} \leq \ell \leq \ell_{\max}\}, \quad (1b)$$

$$u \in \{u \in \mathbb{R}_{(p',q')}^n : u_{\min} \leq u \leq u_{\max}\}, \quad (1c)$$

where $c_{\min}, c_{\max}, \ell_{\min}, \ell_{\max}, u_{\min}, u_{\max} \in \mathbb{R}_{(p',q')}^n$, $c_{\min} \leq c_{\max}$, $\ell_{\min} \leq \ell_{\max}$, $u_{\min} \leq u_{\max}$, and $\mathcal{Q}$ is a compact set. This problem arises in numerous control-related fields, such as MPC problems that can be written in compact form ([Richter, 2012](#)); it can also be applied to a dual setting provided that a compact bound on the dual variables is available ([Patrinos et al., 2015](#)). In particular, we are interested in providing convergence guarantees when implementing the PGM in fixed-point arithmetic. To that

Algorithm 1: PGM applied to $(\mathcal{P}) \in \mathbb{P}$

Input: $x^0 \in \mathcal{X}^0$, $0 < \rho \leq L^{-1}$
1 For each $k = 0, 1, 2, \dots$ **repeat**
2 | $x^{k+1} \leftarrow \mathcal{T}_\rho(x^k) = \min\{u, \max\{\ell, x^k - \rho \nabla f(x^k)\}\}$

end, let us start by recalling the classical “exact” PGM, i.e., its implementation when operating using exact arithmetic.

We denote by $\mathbb{P}$ the set of problems $(\mathcal{P})$ whose ingredients satisfy (1) and $\ell \leq u$. Let $\mathcal{X} \doteq \{x \in \mathbb{R}^n : \ell \leq x \leq u\}$, $f : \mathbb{R}^n \rightarrow \mathbb{R}$ be given by $f(x) = \frac{1}{2}x^\top Qx + c^\top x$, $x^* \in \mathbb{R}^n$ be the optimal solution of problem $(\mathcal{P})$ and f^* its optimal value, i.e., $f^* = f(x^*)$. Let $L, \sigma \in \mathbb{R}^+$ be the largest and smallest smoothness and strong convexity parameters of f for any realization of $(\mathcal{P}) \in \mathbb{P}$, i.e., the scalars for which the well-known inequalities

$$f(x) \leq f(y) + \langle \nabla f(y), x - y \rangle + \frac{L}{2} \|x - y\|^2,$$

$$f(x) \geq f(y) + \langle \nabla f(y), x - y \rangle + \frac{\sigma}{2} \|x - y\|^2,$$

are satisfied $\forall x, y \in \mathbb{R}^n$ for any given $(\mathcal{P}) \in \mathbb{P}$.

Algorithm 1 shows the PGM applied to a realization of problem $(\mathcal{P}) \in \mathbb{P}$, where the min and max operators are taken componentwise and $0 < \rho \leq L^{-1}$. It generates a sequence $\{x^k\} \in \mathcal{X}$ starting at an initial point $x^0 \in \mathcal{X}^0$, where $\mathcal{X}^0 \subseteq \mathcal{X}$ is the set of possible initial guesses. Step 2 of the algorithm performs the operator $\mathcal{T}_\rho : \mathcal{X} \rightarrow \mathcal{X}$ given by

$$\mathcal{T}_\rho(x) \doteq \arg \min_{y \in \mathcal{X}} \frac{1}{2} \|y - (x - \rho \nabla f(x))\|^2,$$

which, when particularized to problem $(\mathcal{P})$, is the evaluation of the proximal operator (Parikh & Boyd, 2013) at $x - \rho \nabla f(x)$. Operator $\mathcal{T}_\rho$ in this setting can also be viewed as the evaluation of the composite gradient mapping (Nesterov, 2013, §2). Furthermore, Algorithm 1 is equivalent in this case to the projected gradient method (Parikh & Boyd, 2013, §4.2).

The following theorem recalls the linear convergence of Algorithm 1 when working under “exact” arithmetic. In the following section we will derive a similar result when operating under fixed-point arithmetic.

Theorem 1 (Theorem 10.29 From Beck (2017)). *Let $\{x^k\}$ be the sequence generated by Algorithm 1 starting at $x^0 \in \mathcal{X}^0$ applied to $(\mathcal{P}) \in \mathbb{P}$. Then,*

- (i) $\|x^k - x^*\|^2 \leq (1 - \rho\sigma)^k \|x^0 - x^*\|^2$, $\forall k \geq 0$,
- (ii) $f(x^k) - f^* \leq \frac{1}{2\rho} (1 - \rho\sigma)^k \|x^0 - x^*\|^2$, $\forall k \geq 1$.

3. Proximal gradient method in fixed-point arithmetic

The maximum number of iterations of Algorithm 1 required to guarantee a given suboptimality can be certified using Theorem 1. Indeed, an immediate result of Theorem 1 is that $\|x^k - x^*\|^2 \leq \epsilon$, for a given $\epsilon \in \mathbb{R}^+$, is satisfied for every iteration k satisfying

$$k \geq \frac{\log\left(\frac{\epsilon}{\|x^0 - x^*\|^2}\right)}{\log(1 - \rho\sigma)}. \quad (2)$$

We are now interested in providing an iteration and suboptimality certification when Algorithm 1 is implemented using fixed-point arithmetic. Therefore, let us consider Algorithm 1 when working under fixed-point arithmetic for some predetermined choice of integer and fractional precision (p, q) satisfying $p \geq p'$ and $q \geq q'$, where we recall that (p', q') is the precision

Algorithm 2:

 PGM applied to $(\mathcal{P}) \in \mathbb{P}$ under fixed-point arithmetic with precision (p, q)

Input: $\hat{x}^0 \in \hat{\mathcal{X}}^0_{(p,q)}$, $0 < \rho \leq L^{-1}$, $\hat{\epsilon} \in \mathbb{R}^+_{(p,q)}$, $k_{\max} \in \mathbb{R}^+$
1 For each $k = 0, 1, 2, \dots$ **repeat**
2 | $\hat{x}^{k+1} \leftarrow \min\{u, \max\{\ell, \hat{x}^k - \hat{g}_\rho(\hat{x}^k)\}\}$
3 until $\hat{d}^2(\hat{x}^k) < \hat{\epsilon}$ or $k \geq k_{\max}$

under which the ingredients of $(\mathcal{P})$ are representable. Under this paradigm, we can view the implementation of the PGM algorithm as performing an inexact proximal operator, where the source of inexactness is due to the fixed-point arithmetic and representation of variables.

Algorithm 2 shows the implementation of Algorithm 1 under fixed-point arithmetic. It generates a sequence of iterates $\{\hat{x}^k\} \in \mathcal{X}_{(p,q)}$ starting from an initial point $\hat{x}^0 \in \hat{\mathcal{X}}^0_{(p,q)} \subseteq \mathcal{X}_{(p,q)}$. Step 2 evaluates the operator $\hat{g}_\rho : \mathcal{X}_{(p,q)} \rightarrow \mathcal{X}_{(p,q)}$, which is defined as the operator that performs the computation of $\rho \nabla f(\cdot)$ in the fixed-point paradigm. That is, $\hat{g}_\rho(\hat{x}^k)$ returns the result of the evaluation of $\rho \nabla f(\hat{x}^k)$ when performed under fixed-point arithmetic. Thus, $\rho \in \mathbb{R}^+_{(p,q)}$ is an obvious requirement of Algorithm 2. Additionally, the algorithm includes an exit condition given by the satisfaction of the condition $\hat{d}^2(\hat{x}^k) < \hat{\epsilon}$, where $\hat{d}^2 : \mathcal{X}_{(p,q)} \rightarrow \mathbb{R}^+_{(p,q)} \cup \{0\}$ is the operator that performs the computation of $\|\hat{x}^{k+1} - \hat{x}^k\|^2$ in fixed-point arithmetic. This exit condition plays a key role in the suboptimality guarantees provided in this section.

The value of $\hat{g}_\rho(\hat{x}^k)$ will generally differ from the exact value of the expression $\rho \nabla f(\hat{x}^k)$ due to the arithmetic errors that occur when using fixed-point arithmetic, thus leading to the source of discrepancy between the sequences generated by Algorithms 1 and 2. The magnitude of this discrepancy, which we formalize in the following definition, will depend on the value of the fractional precision q , with higher values of q obviously leading to smaller errors.

Definition 1. Given a choice of q , we denote by $\Omega \in \mathbb{R}^+$ a scalar satisfying $\|\rho \nabla f(\hat{x}) - \hat{g}_\rho(\hat{x})\| \leq \Omega$, $\forall \hat{x} \in \mathcal{X}_{(p,q)}$, $\forall (\mathcal{P}) \in \mathbb{P}$.

The rest of the operations in Step 2 of Algorithm 2 do not incur any additional error, as formally stated in the following lemma, so they do not contribute towards the discrepancy between the “exact” and “fixed-point” implementations.

Lemma 1. Let $\underline{v}, \bar{v}, \hat{x}, \hat{y} \in \mathbb{R}^n_{(p,q)}$, with $\underline{v} \leq \bar{v}$, and consider the set $\mathcal{C} \doteq \{v \in \mathbb{R}^n : \underline{v} \leq v \leq \bar{v}\}$. Then, the result of the fixed-point computations $\min\{\bar{v}, \max\{\underline{v}, \hat{x} + \hat{y}\}\}$ performed with any precision $(\hat{p}, \hat{q})$ satisfying $\hat{p} \geq p$ and $\hat{q} \geq q$ is the exact Euclidean projection of $\hat{x} + \hat{y}$ onto $\mathcal{C}$ if $\hat{x} + \hat{y}$ does not result in an overflow.

The proof of the lemma is omitted because the claim is a direct result of the fact that the min, max and addition operations do not incur in any error under fixed-point arithmetic as long as there is no overflow in the addition.

Corollary 1. Variable $\hat{x}^{k+1}$ obtained from Step 2 of Algorithm 2 is the exact Euclidean projection of $\hat{x}^k - \hat{g}_\rho(\hat{x}^k)$ onto $\mathcal{X}$, assuming that no overflow occurs during the computations. Therefore, $\hat{x}^k \in \mathcal{X}_{(p,q)} \subset \mathcal{X}$, $\forall k \geq 0$.

The reader will note that Lemma 1 is only applicable to Algorithm 2 as long as there is no overflow during its execution, i.e., if the integer precision p is large enough. The certification tool presented in Section 4 can be used to compute the minimum value of p required to avoid overflow. Thus, we henceforth simply consider that p is chosen so that no overflow occurs during the execution of Algorithm 2.

Another useful consequence of [Lemma 1](#) is presented in the following lemma, which states that a scalar Ω satisfying [Definition 1](#) also bounds the error in the computation of $\hat{x}^{k+1}$.

Lemma 2. Consider Algorithm 2 and let Ω satisfy [Definition 1](#). Then, $\|\hat{x}^{k+1} - \mathcal{T}_\rho(\hat{x}^k)\| \leq \Omega$, $\forall \hat{x}^k \in \mathcal{X}_{(p,q)}$, $\forall (\mathcal{P}) \in \mathbb{P}$.

Proof. The claim is a direct consequence of [Corollary 1](#) and the fact that the projection operator to non-empty closed convex sets is non-expansive ([Ryu & Boyd, 2016, §3.1](#)). ■

We now present the main result of this section, where we characterize the local linear convergence of Algorithm 2, in terms of the error-bound Ω , when sufficiently far away from the optimal solution.

Theorem 2. Let $\{\hat{x}^k\}$ be the sequence generated by Algorithm 2 applied to a realization of problem $(\mathcal{P}) \in \mathbb{P}$ with starting point $\hat{x}^0 \in \hat{\mathcal{X}}_{(p,q)}^0$ and taking $0 < \rho \leq L^{-1}$, $\rho \in \mathbb{R}_{(p,q)}$. Choose $\epsilon \in \mathbb{R}^+$ satisfying $\epsilon \rho \sigma > 4\Omega$, where $\Omega \in \mathbb{R}^+$ is given by [Definition 1](#). Then, as long as $\|\hat{x}^{k+1} - x^*\| \geq \frac{\epsilon}{2}$, the sequence $\{\hat{x}^k\}$ satisfies:

- (i) $\|\hat{x}^k - x^*\|^2 \leq \left(\frac{1 - \rho\sigma}{1 - 4\Omega\epsilon^{-1}} \right)^k \|\hat{x}^0 - x^*\|^2$, $\forall k \geq 0$.
- (ii) $f(\hat{x}^k) - f^* \leq \frac{1 - 4\Omega\epsilon^{-1}}{2\rho} \left(\frac{1 - \rho\sigma}{1 - 4\Omega\epsilon^{-1}} \right)^k \|\hat{x}^0 - x^*\|^2$, $\forall k \geq 1$.

Proof. See the [Appendix](#). ■

[Theorem 2](#) provides a linear convergence result similar to the one shown in [Theorem 1](#), but where the convergence constant degrades by the factor $(1 - 4\Omega\epsilon^{-1})$. That is, the convergence guarantee worsens as Ω increases and as the desired suboptimality tolerance ϵ decreases. Since the theorem only holds as long as $\|\hat{x}^{k+1} - x^*\| \geq \frac{\epsilon}{2}$, we need to be able to check the satisfaction of this condition during the execution of Algorithm 2.

Lemma 3. $\|\hat{x} - \mathcal{T}_\rho(\hat{x})\| \leq 2\|\hat{x} - x^*\|$, $\forall \hat{x} \in \mathcal{X}$.

Proof. From ([Alamo et al., 2019, Property 1.\(i\)](#)), particularized to our problem formulation and notation, we have that

$$f(\mathcal{T}_\rho(\hat{x})) - f^* \leq \rho^{-1} \langle \hat{x} - \mathcal{T}_\rho(\hat{x}), \hat{x} - x^* \rangle - \frac{1}{2\rho} \|\hat{x} - \mathcal{T}_\rho(\hat{x})\|^2,$$

which along with $f(\mathcal{T}_\rho(\hat{x})) - f^* \geq 0$, leads to

$$\frac{1}{2} \|\hat{x} - \mathcal{T}_\rho(\hat{x})\|^2 \leq \langle \hat{x} - \mathcal{T}_\rho(\hat{x}), \hat{x} - x^* \rangle \leq \|\hat{x} - \mathcal{T}_\rho(\hat{x})\| \cdot \|\hat{x} - x^*\|$$

by making use of the Cauchy–Schwarz inequality. ■

The previous lemma allows us to guarantee that the condition $\|\hat{x}^k - x^*\| \geq \frac{\epsilon}{2}$ in [Theorem 2](#) holds for the iterates of Algorithm 2 as long as we can guarantee that $\|\hat{x}^k - \mathcal{T}_\rho(\hat{x}^k)\| \geq \epsilon$. The following assumption allows us to use the exit condition of Algorithm 2 as a means to guarantee that the condition $\|\hat{x}^k - x^*\| \geq \frac{\epsilon}{2}$ is satisfied at iteration k .

Assumption 1. The exit tolerance $\hat{\epsilon}$ of Algorithm 2 satisfies $\hat{d}^2(\hat{x}^k) \geq \hat{\epsilon} \implies \|\hat{x}^k - \mathcal{T}_\rho(\hat{x}^k)\|^2 \geq \epsilon^2$.

In the following section we present a tractable procedure for certifying the satisfaction of this assumption. In practice, we find that one can choose ϵ so that the smallest value of $\hat{\epsilon}$ satisfying

[Assumption 1](#) is the smallest positive representable number in precision q , i.e., 2^{-q} . In this case the exit condition of Algorithm 2 becomes $\hat{d}^2(\hat{x}^k) = 0$.

Under [Assumption 1](#), the convergence guarantee provided in [Theorem 2](#) holds as long as the exit condition $\hat{d}^2(\hat{x}^k) < \hat{\epsilon}$ is not satisfied. If it is satisfied at some iteration k , then the convergence guarantee provided by [Theorem 2](#) is only guaranteed to hold until iteration $k - 1$. The following theorem provides the suboptimality guarantees of Algorithm 2 when the exit condition is satisfied at some iteration k . The result makes use of the bounds provided in the following definition. The following section will provide computationally tractable procedures for computing arbitrarily tight values of said bounds.

Definition 2. Consider Algorithm 2. For a given choice of fractional precision q and tolerance $\hat{\epsilon}$, we denote by δ , ω , $\Theta \in \mathbb{R}^+$ the scalars satisfying

$$\|\hat{x}^k - \mathcal{T}_\rho(\hat{x}^k)\| \leq \delta, \quad \|\hat{x}^{k+1} - \mathcal{T}_\rho(\hat{x}^k)\| \leq \omega, \quad \|\hat{x}^k - \hat{x}^{k+1}\| \leq \Theta$$

for all $\hat{x}^k \in \mathcal{X}_{(p,q)}$ satisfying $\hat{d}^2(\hat{x}^k) < \hat{\epsilon}$, $\forall (\mathcal{P}) \in \mathbb{P}$.

Theorem 3. Let $\{\hat{x}^k\}$ be the sequence generated by Algorithm 2 applied to a realization of problem $(\mathcal{P}) \in \mathbb{P}$ with starting point $\hat{x}^0 \in \hat{\mathcal{X}}_{(p,q)}^0$ and taking $0 < \rho \leq L^{-1}$, $\rho \in \mathbb{R}_{(p,q)}$. Denote $T \doteq \sigma^{-1}(\rho^{-1} + L)$. Then, if $\hat{d}^2(\hat{x}^k) < \hat{\epsilon}$,

- (i) $\|\hat{x}^{k+1} - x^*\| \leq \omega + \delta T$,
- (ii) $f(\hat{x}^{k+1}) - f^* \leq \rho^{-1} \left((\Theta + \Omega)(\omega + \delta T) + \frac{1}{2} \Theta^2 \right)$.

Proof. From ([Nesterov, 2013, Lemma 3](#)), particularized to our notation, we have that $\|\hat{x}^k - \mathcal{T}_\rho(\hat{x}^k)\| \geq T^{-1} \|\mathcal{T}_\rho(\hat{x}^k) - x^*\|$, which leads to $\|\hat{x}^k - \mathcal{T}_\rho(\hat{x}^k)\| \leq \delta \implies \|\mathcal{T}_\rho(\hat{x}^k) - x^*\| \leq T\delta$. Claim (i) follows from adding the previous inequality with $\|\hat{x}^{k+1} - \mathcal{T}_\rho(\hat{x}^k)\| \leq \omega$ and applying the triangle inequality. By the same procedure, we also derive $\|\hat{x}^k - x^*\| \leq \delta(T + 1)$. Claim (ii) then follows from particularizing [Lemma 5.\(i\)](#) to $y = x^*$, using the Cauchy–Schwarz inequality and then taking the previous inequalities along with the inequalities presented in [Definitions 1](#) and [2](#). ■

The following corollary gathers the guarantees that are obtained from Algorithm 2 in terms of the error-bounds and tolerances presented throughout this section.

Corollary 2 (Suboptimality Guarantee of Algorithm 2). Let $k_{\max} \geq \log\left(\frac{\epsilon^2}{4D}\right) / \log(C)$, where $C \doteq \frac{1 - \rho\sigma}{1 - 4\Omega\epsilon^{-1}}$ and D satisfies $D \geq \max_{\hat{x} \in \hat{\mathcal{X}}_{(p,q)}^0} \|\hat{x} - x^*\|^2$. The following hold:

- (i) If $\hat{d}^2(\hat{x}^k) \geq \hat{\epsilon}$ for all $k = \{0, \dots, k_{\max}\}$, then

$$\|\hat{x}^{k_{\max}} - x^*\| \leq \frac{\epsilon}{2} \quad \text{and} \quad f(\hat{x}^{k_{\max}}) - f^* \leq \frac{(\epsilon^2 - 4\Omega\epsilon)}{8\rho}.$$
- (ii) If $\hat{d}^2(\hat{x}^k) < \hat{\epsilon}$ then $\|\hat{x}^{k+1} - x^*\| \leq \omega + \delta T$ and

$$f(\hat{x}^{k+1}) - f^* \leq \rho^{-1} \left((\Theta + \Omega)(\omega + \delta T) + \frac{1}{2} \Theta^2 \right).$$

Remark 1. From [Lemma 2](#) we have that the bound ω from [Definition 2](#) can be substituted by Ω from [Definition 1](#). We find that for high fractional precision there can be an insignificant difference between the two quantities, thus not meriting the additional computation time required to compute ω .

Algorithm 3: Example of input algorithm for formal verification

Parameters: $(p.q)$, $b \in \mathbb{R}_{(p.q)}$, $\hat{a} \in \mathbb{R}^+$, $\xi \in \mathbb{R}$, $\chi \in \mathbb{R}^+$
Non-deterministic: $a \in \mathcal{A} = \{a \in \mathbb{R}^m : \|a\|_\infty \leq \hat{a}\}$

```

1  $r = \langle a, a \rangle$ 
2  $\mu = br$ 
3 if  $|\text{err}(r)| > \chi$  then FAIL
4 if  $\text{exact}(\mu) < \xi$  then FAIL

```

4. Obtaining error-bounds for Algorithm 1

This section presents procedures for obtaining arbitrarily tight values of the bounds Ω , δ , ω and Θ introduced in [Definitions 1](#) and [2](#) as well as a procedure for checking the satisfaction of [Assumption 1](#). The procedures consist on the application of the formal verification procedure presented in [Simić et al. \(2022\)](#) to check the conditions provided in the definitions and assumption. We first introduce the formal analysis technique for fixed-point arithmetic, and then show how it fits within our certification process.

4.1. Formal verification for fixed-point arithmetic

[Simić et al. \(2022\)](#) consider the problem of estimating the numerical accuracy of algorithms in fixed-point arithmetic with variables of arbitrary precision and possibly non-deterministic values. The idea is to re-compute in a greater precision the result of each fixed-point operation, so that the numerical error can be estimated based on the difference between the two values; at the same time, the different errors are in turn accounted for and propagated through the re-computations. When sufficient precision is used to store the re-computed values, this yields an accurate error tracking for each variable at any point of the computation. The technique relies on a bit-precise encoding to transform the sequences of operations under analysis into operations in integer arithmetic over vectors of bits; these are in turn encoded as a SAT formula that is satisfiable if and only if the algorithm under analysis exceeds a given bound on the numerical error. The technique is quite accurate in that it allows to formally verify arbitrarily tight bounds on the numerical error up to a given number of iterations. On the other hand, the required program unfolding pass along with the bit-vector encoding ends up introducing considerable overhead; the analysis can become quickly intractable, even for small problems and a few iterations. We note that this is not a problem in our case, as the algorithms that we need to analyze have been formulated so as to only require a single iteration.

We now provide an illustrative example to introduce the concepts and notation relevant to this article. Consider [Algorithm 3](#) working under a given fixed-point precision $(p.q)$, where r is a fixed-point variable, $\text{exact}\{r\}$ is its “exact” counterpart and $\text{err}\{r\}$ is its error, i.e., $\text{exact}\{r\} = r + \text{err}\{r\}$. The same applies for the other variables, such as μ , whose exact value will generally differ from its value computed in fixed-point arithmetic due to the multiplication operations. The error of r is propagated when computing the error of μ , i.e., $\text{exact}\{\mu\}$ will contain the value of $\langle a, a \rangle$. We can perform assessments on the fixed-point variables, their errors and their exact values (as shown in [Steps 3](#) and [4](#)) for all possible values of the non-deterministic inputs (variable a in this case). If all the assessments are satisfied for all possible values of the non-deterministic variables then the procedure will return a PASS. Otherwise, it will return a FAIL.

Algorithm 4: Algorithm for asserting [Assumption 1](#)

Parameters: $(p.q)$, $\hat{\epsilon}$, ϵ^2
Non-deterministic: $\hat{x}^0 \in \mathcal{X}_{(p.q)}$, $(\mathcal{P}) \in \mathbb{P}$

```

1  $\hat{x}^{k+1} \leftarrow \min\{u, \max\{\ell, \hat{x}^k - \hat{g}_\rho(\hat{x}^k)\}\}$ 
2  $d \leftarrow \langle \hat{x}^k - \hat{x}^{k+1}, \hat{x}^k - \hat{x}^{k+1} \rangle$ 
3 if  $d \geq \hat{\epsilon}$  and  $\text{exact}\{d\} < \epsilon^2$  then FAIL

```

Algorithm 5: Algorithm for deriving Ω

Parameters: $(p.q)$, Ω^2
Non-deterministic: $\hat{x}^0 \in \mathcal{X}_{(p.q)}$, $(\mathcal{P}) \in \mathbb{P}$

```

1  $\hat{g} \leftarrow \rho(Q\hat{x}^0 + c)$ 
2  $e \leftarrow \text{err}\{\hat{g}\}$ 
3  $v \leftarrow \langle e, e \rangle$ 
4 if  $\text{exact}\{v\} > \Omega^2$  then FAIL

```

Algorithm 6: Algorithm for deriving [Definition 2](#) bounds

Select: $b \in \{\delta^2, \omega^2, \Theta^2\}$
Parameters: $(p.q)$, $\hat{\epsilon}$
Non-deterministic: $\hat{x}^0 \in \mathcal{X}_{(p.q)}$, $(\mathcal{P}) \in \mathbb{P}$

```

1  $\hat{x}^{k+1} \leftarrow \min\{u, \max\{\ell, \hat{x}^k - \hat{g}_\rho(\hat{x}^k)\}\}$ 
2 if  $\langle \hat{x}^k - \hat{x}^{k+1}, \hat{x}^k - \hat{x}^{k+1} \rangle < \hat{\epsilon}$  then
3   switch  $b$  do
4     case  $\delta^2$  do  $s \leftarrow \hat{x}^k - \hat{x}^{k+1}$ 
5     case  $\omega^2$  do  $s \leftarrow \text{err}\{\hat{x}^{k+1}\}$ 
6     case  $\Theta^2$  do
7        $\text{err}\{\hat{x}^{k+1}\} \leftarrow 0$ 
8        $s \leftarrow \hat{x}^k - \hat{x}^{k+1}$ 
9     end case
10  end switch
11 end if
12  $v \leftarrow \langle s, s \rangle$ 
13 if  $\text{exact}\{v\} > b$  then FAIL

```

Example 1. We run the verification procedure presented in [Simić et al. \(2022\)](#) on [Algorithm 3](#) with $p = 8$, $q = 8$, $m = 20$, $\hat{a} = 0.125$, $b = 1.5$, $\xi = 0$, and $\chi = 0.069580078125$. We obtain a PASS, that is, there is no value of a inside the box defined by $\hat{a}$ for which the assertions stated in [Steps 3](#) and [4](#) of [Algorithm 3](#) are violated. The result of this example highlights one of the main benefit of this procedure, which is the bound $\chi = 0.069580078125$. Variable r is the inner product of a by itself. As stated in [Patrinos et al. \(2015\)](#), the standard theoretical bound for the maximum error committed by an inner product is given by $\text{err}(\langle a, a \rangle) \leq 2^{-q}m$, which is equal to 0.078125 for the values of q and m in this example. However, the formal verification procedure has found that this theoretical bound can be improved to $\text{err}(\langle a, a \rangle) = 0.069580078125$, which is a 12.28% improvement. That is, the procedure may lead to tighter bounds on the errors committed by the fixed-point algorithm than the ones obtained by simply evaluating its execution under the theoretical worst-case scenario. The procedure finishes after $\sim 5s$ using a standard machine with an Intel i5 processor.

4.2. Verification procedure for Algorithm 2

The application of the verification tool presented in the previous subsection to [Algorithm 4](#) certifies if the given $\hat{\epsilon}$ and ϵ^2

Table 1

Bounds obtained from the verification procedures for the three-mass-spring case study.

Bound b	Value	b^2	Tol.	# P/F	Av. PASS time [s]	Av. FAIL time [s]	Total time [s]
Ω	$1.711 \cdot 10^{-6}$	2^{-2q}	10^{-14}	4/8	218.1	982.8	8738.8
ϵ	$6.8949 \cdot 10^{-4}$	$(4\Omega/(\rho\sigma))^2$	10^{-9}	11/4	73.8	75.2	1117.4
δ	$1.383 \cdot 10^{-3}$	2^{-q}	10^{-9}	10/4	84.7	90.8	1215.0
Θ	$1.381 \cdot 10^{-3}$	δ^2	10^{-9}	3/8	12.1	28.3	266.6

satisfy [Assumption 1](#). Its application to [Algorithms 5](#) certifies if the provided value of Ω satisfies the condition presented in [Definition 1](#). A PASS indicates that the given Ω^2 satisfies the condition $\|\mathcal{T}_\rho(\hat{x}^k) - \hat{x}^{k+1}\|^2 \leq \Omega^2$, $\forall \hat{x}^k \in \mathcal{X}_{(p,q)}$, $\forall (\mathcal{P}) \in \mathbb{P}$, whereas a FAIL indicates that there is at least one combination of $\hat{x}^k \in \mathcal{X}_{(p,q)}$ and $(\mathcal{P}) \in \mathbb{P}$ for which the condition is not satisfied. Note that the condition is asserted with respect to Ω^2 , since the verification tool does not allow the use of the square-root operation. Similarly, for a given value of $\hat{\epsilon}$, [Algorithm 6](#) is used to certify if the bounds δ , ω or Θ satisfy the conditions presented in [Definition 2](#). Arbitrarily tight values of Ω , δ , ω or Θ can be obtained by applying the bisection method to [Algorithms 5](#) and [6](#). Note that [Algorithms 4](#), [5](#) and [6](#) only execute a single iteration of [Algorithm 2](#). Thus, the proposed verification procedure remains tractable for moderately-sized problems, in contrast with the approach taken in [Simić et al. \(2022\)](#).

Remark 2. The verification tool from [Simić et al. \(2022\)](#) can be configured to return a FAIL in the event of a numerical overflow. Thus, we can verify that no overflow occurs in [Algorithm 2](#) for a given choice of the integer precision p if the tool does not fail due to an overflow when applied to [Algorithm 4](#).

5. Numerical case study

We apply the verification procedures presented in the previous section to certify the fixed-point implementation of the PGM to solve the optimization problem of a linear MPC controller for a discrete-time, time-invariant system given by a state-space model $\tilde{x}(t) = A\tilde{x}(t) + B\tilde{u}(t)$, where $\tilde{x}(t) \in \mathbb{R}^{n_x}$ and $\tilde{u}(t) \in \mathbb{R}^{n_u}$ are the state and control input at sample time t .

In particular, we consider the system of three masses connected by springs presented in [Krupa, Jaouani et al. \(2021, §3\)](#), where we take the mass all three objects equal to 1kg and the spring constants as 1 N/m. The 6-dimensional system state is given by the position and velocity of each of the three objects, while the control input is given by the two external forces applied to the outer objects. We take the following MPC formulation:

$$\min \sum_{i=0}^{N_p-1} (\|\tilde{x}_i - \tilde{x}_r\|_{W_x}^2 + \|\tilde{u}_i - \tilde{u}_r\|_{W_u}^2) + \|\tilde{x}_{N_p} - \tilde{x}_r\|_P^2 \quad (3a)$$

$$\text{s.t. } \tilde{x}_0 = \tilde{x}(t) \quad (3b)$$

$$\tilde{x}_{i+1} = A\tilde{x}_i + B\tilde{u}_i, \quad \forall i \in \mathbb{Z}_0^{N_p-1} \quad (3c)$$

$$\tilde{u}_i = \tilde{u}_{N_c-1}, \quad \forall i \in \mathbb{Z}_{N_c}^{N_p-1} \quad (3d)$$

$$\tilde{u}_- \leq \tilde{u}_i \leq \tilde{u}_+, \quad \forall i \in \mathbb{Z}_0^{N_c-1}, \quad (3e)$$

where $N_c \in \mathbb{R}^+$ is the control horizon; $N_p \geq N_c$ is the prediction horizon; $W_x, P \in \mathbb{R}^{n_x \times n_x}$ and $W_u \in \mathbb{R}^{n_u \times n_u}$ are positive definite; (x_r, u_r) are the state and input references; and $\tilde{u}_-, \tilde{u}_+ \in \mathbb{R}^{n_u}$ satisfying $\tilde{u}_- \leq \tilde{u}_+$ define the bounds on the control input. We take $N_c = 2$, $N_p = 5$, $\tilde{u}_+ = (0.5, 0.5)$, $\tilde{u}_- = -\tilde{u}_+$, $W_x = 0.5I_{n_x}$, $W_u = 0.25I_{n_u}$ and P as the solution of the associated discrete algebraic Riccati equation. Problem (3) can be transformed into [\(P\)](#) by eliminating the states and rewriting it in condensed form, see e.g., [Jerez et al. \(2011\)](#) and [Richter \(2012\)](#), leading to a $(n_u N_c)$ -dimensional QP problem. In this case, ingredients Q , ℓ and u of

problem [\(P\)](#) are fixed, whereas the value of c will depend on the value of the reference (x_r, u_r) as well as the current state $\tilde{x}(t)$. We compute $c_{\min}$ and $c_{\max}$ by assuming that the position of the objects belong to the interval $[-0.5, 0.5]$ m and the velocities to $[-1, 1]$ m/s. A non-deterministic Q would be taken if we allowed the possibility of changing the weight W_u online or if we considered a time-varying model of the system.

We now certify the PGM applied to the resulting condensed MPC problem when implemented in fixed-point arithmetic on a 32-bit device, where we take $p = 10$ for the integer precision and $q = 21$ for the fractional precision (the remaining bit is used for storing the sign). We store the matrices of the QP problem in the selected precision. The resulting problem has $L = 4.9645$ and $\sigma = 0.3532$. We take ρ as the largest number representable in $\mathbb{R}_{(p,q)}$ that satisfies $\rho \leq 1/L$.

In our formal verification procedure we used the prototype tool of [Simić et al. \(2022\)](#) for generating the bit-vector encoding, CBMC 5.4 ([Clarke et al., 2004](#)) for generating the SAT formula from the bit-vector encoding and MiniSat ([Eén & Sörensson, 2004](#)) to check for the satisfiability of the SAT formula. All computations are performed on an Intel i5 processor running at 1.6 GHz. We start by computing the value of Ω by selecting an initial value of Ω^2 and then applying the bisection method on the verification of [Algorithm 5](#) with an exit tolerance of 10^{-14} , i.e., until the difference between the largest and smallest values of Ω^2 resulting in a FAIL and a PASS, respectively, is smaller than 10^{-14} . [Table 1](#) shows the value of Ω obtained from this procedure, along with the selected exit tolerance, initial guess of Ω^2 , number of tests resulting in a PASS, number of tests resulting in a FAIL, average computation times of calls resulting in a PASS or FAIL, and total computation time of the bisection method. We take $\hat{\epsilon} = 2^{-q}$, which is the smallest value it can take, and then find the largest value of ϵ satisfying [Assumption 4](#) by applying the bisection method on [Algorithm 4](#). The results are presented in [Table 1](#), where we note that the value of ϵ satisfies $\epsilon > 4\Omega/(\rho\sigma) = 9.6195 \cdot 10^{-5}$. Therefore, we can use the exit condition $\hat{d}^2(\hat{x}^k) = 0$. Finally, we obtain the bounds δ and Θ following the same bisection procedure used to compute Ω . The results are also presented in [Table 1](#). We take $\omega = \Omega$, as stated in [Remark 1](#).

Plugging the results into [Corollary 2.2](#), we obtain the following: $k_{\max} = 250$, if $\hat{d}^2(\hat{x}^k) = 0$ then $\|\hat{x}^{k+1} - x^*\| \leq 0.0389$ and $f(\hat{x}^{k+1}) - f^* \leq 2.7165 \cdot 10^{-4}$, are the best suboptimality bounds that can be guaranteed, since the ones from [Corollary 2.2](#) are smaller. The value of $k_{\max}$ required to obtain the same $\epsilon/2$ -suboptimality under exact arithmetic is 217, c.f., [\(2\)](#).

6. Conclusions

This article has presented a procedure for certifying the implementation of the PGM under fixed-point arithmetic when applied to strongly-convex box-constrained QP problems. We have proven that the PGM maintains a linear convergence guarantee when sufficiently far away from the optimal solution, indicated by the choice of ϵ , whose value can be reduced up to a maximum bound given by the fixed-point error-bound. We have then presented a procedure based on recent formal verification tools to obtain a arbitrarily tight values of this error-bound and the other bounds that characterize the suboptimality of the output of the

PGM. Finally, we have shown that the computation times of the proposed verification procedures are tractable for a non-trivial MPC example.

Appendix. Proofs and auxiliary lemmas

We start by providing two lemmas whose results are used in the proofs of [Theorems 2](#) and [3](#).

Lemma 4. Consider [Algorithm 2](#). For any $\alpha \in \mathbb{R}^+$,

$$\alpha(\hat{x}^k - \hat{x}^{k+1} - \hat{g}_\rho(\hat{x}^k)) \in \partial \mathcal{I}_\mathcal{X}(\hat{x}^{k+1}), \quad \forall k \geq 0.$$

Proof. The claim follows from $\hat{x}^{k+1}$ being the Euclidean projection of $\hat{x}^k - \hat{g}_\rho(\hat{x}^k)$ onto $\mathcal{X}$ (see [Corollary 1](#)) along with the optimality condition of the projection operator ([Bertsekas, 2009](#), Prop. 5.4.7) and the equivalence between the subdifferential of the indicator function of a non-empty convex set and its normal cone ([Bertsekas, 2009](#), Example 5.4.1). ■

The following lemma particularizes ([Alamo et al., 2019](#), Property 1) to the fixed-point PGM paradigm.

Lemma 5. Consider [Algorithm 2](#) and let $v^k \in \mathcal{B}_\Omega^n$ be the vectors that satisfy $\rho \nabla f(\hat{x}^k) = \hat{g}_\rho(\hat{x}^k) + v^k$ for every $k \geq 0$. Denote $s^k \doteq \hat{x}^k - \hat{x}^{k+1}$. Then, $\forall y \in \mathbb{R}^n$,

$$f(\hat{x}^{k+1}) - f(y) \leq \rho^{-1} \langle s^k + v^k, \hat{x}^{k+1} - y \rangle + \frac{1}{2\rho} \|s^k\|^2 \quad (i)$$

$$= \rho^{-1} \langle s^k, \hat{x}^k - y \rangle - \frac{1}{2\rho} \|s^k\|^2 + \rho^{-1} \langle v^k, \hat{x}^{k+1} - y \rangle \quad (ii)$$

$$= \frac{1}{2\rho} \|\hat{x}^k - y\|^2 - \frac{1}{2\rho} \|\hat{x}^{k+1} - y\|^2 + \rho^{-1} \langle v^k, \hat{x}^{k+1} - y \rangle. \quad (iii)$$

Proof. From [Lemma 4](#) we have that $\rho^{-1}(\hat{x}^k - \hat{x}^{k+1} - \hat{g}_\rho(\hat{x}^k)) \in \partial \mathcal{I}_\mathcal{X}(\hat{x}^{k+1})$. Therefore, from the definition of the subdifferential ([Parikh & Boyd, 2013](#), §2.3), we have that

$$\mathcal{I}_\mathcal{X}(y) \geq \mathcal{I}_\mathcal{X}(\hat{x}^{k+1}) + \rho^{-1} \langle \hat{x}^k - \hat{x}^{k+1} - \hat{g}_\rho(\hat{x}^k), y - \hat{x}^{k+1} \rangle,$$

where taking $y \in \mathcal{X}$ and recalling that $\hat{x}^{k+1} \in \mathcal{X}$ (see [Corollary 1](#)), leads to

$$0 \geq \rho^{-1} \langle \hat{x}^k - \hat{x}^{k+1} - \hat{g}_\rho(\hat{x}^k), y - \hat{x}^{k+1} \rangle. \quad (A.4)$$

From the convexity of f we have that

$$f(y) \geq f(\hat{x}^k) + \langle \nabla f(\hat{x}^k), y - \hat{x}^k \rangle. \quad (A.5)$$

Additionally, from the L -smoothness of f and since $\rho \leq L^{-1}$, we have that

$$f(\hat{x}^k) \geq f(\hat{x}^{k+1}) - \langle \nabla f(\hat{x}^k), \hat{x}^{k+1} - \hat{x}^k \rangle - \frac{1}{2\rho} \|s^k\|^2. \quad (A.6)$$

Claim (i) follows from adding (A.4), (A.5) and (A.6) along with the definition of v^k . Claims (ii) and (iii) then follow from simple algebraic manipulations; c.f. Property 1.(i) in [Alamo et al. \(2019\)](#). ■

We now present the proof of [Theorem 2](#), which closely follows the proofs of ([Beck, 2017](#), Theorem 10.16 and Theorem 10.29), although various modifications have to be made to extend the results to the fixed-point arithmetic paradigm.

Proof of Theorem 2. Let $s^k \doteq \hat{x}^{k+1} - \hat{x}^k$ and $\gamma^k \doteq \hat{x}^k - x^*$. Consider the function $\psi : \mathcal{X} \rightarrow \mathbb{R}$ given by

$$\psi(y) = f(\hat{x}^k) + \langle \nabla f(\hat{x}^k), y - \hat{x}^k \rangle + \mathcal{I}_\mathcal{X}(y) + \frac{1}{2\rho} \|y - \hat{x}^k\|^2.$$

Since ψ is an ρ^{-1} -strongly convex function, it follows from ([Beck, 2017](#), Theorem 5.24) that

$$\psi(y) - \psi(\hat{x}^{k+1}) \geq \langle \mu, y - \hat{x}^{k+1} \rangle + \frac{1}{2\rho} \|y - \hat{x}^{k+1}\|^2, \quad (A.7)$$

$\forall \hat{x}^{k+1} \in \mathcal{X}_{(p,q)}$, $\forall \mu \in \partial \psi(\hat{x}^{k+1})$. Since $\rho \leq L^{-1}$, we have that $f(\cdot)$ satisfies the well-known descent lemma ([Beck, 2017](#), Lemma 5.7)

$$f(\hat{x}^{k+1}) \leq f(\hat{x}^k) + \langle \nabla f(\hat{x}^k), \hat{x}^{k+1} - \hat{x}^k \rangle + \frac{1}{2\rho} \|\hat{x}^{k+1} - \hat{x}^k\|^2,$$

$\forall \hat{x}^{k+1} \in \mathcal{X}_{(p,q)}$, $\forall y \in \mathcal{X}$, which along with the definition of ψ and noting that $\mathcal{I}_\mathcal{X}(\hat{x}^{k+1}) = 0$ by virtue of [Corollary 1](#), leads to

$$\psi(\hat{x}^{k+1}) = f(\hat{x}^k) + \langle \nabla f(\hat{x}^k), s^k \rangle + \frac{1}{2} \|s^k\|^2 \geq f(\hat{x}^{k+1}),$$

$\forall \hat{x}^{k+1} \in \mathcal{X}_{(p,q)}$. Thus, we can rewrite (A.7) as

$$\psi(y) - f(\hat{x}^{k+1}) \geq \langle \mu, y - \hat{x}^{k+1} \rangle + \frac{1}{2\rho} \|y - \hat{x}^{k+1}\|^2, \quad (A.8)$$

$\forall \hat{x}^{k+1} \in \mathcal{X}_{(p,q)}$, $\forall \mu \in \partial \psi(\hat{x}^{k+1})$. The subdifferential of ψ evaluated at $\hat{x}^{k+1}$ is given by

$$\partial \psi(\hat{x}^{k+1}) = \nabla f(\hat{x}^k) + \rho^{-1}(\hat{x}^{k+1} - \hat{x}^k) + \partial \mathcal{I}_\mathcal{X}(\hat{x}^{k+1}). \quad (A.9)$$

From [Definition 1](#) we have that for each $k \geq 0$ there exists a vector $v^k \in \mathcal{B}_\Omega^n$ satisfying $\rho \nabla f(\hat{x}^k) = \hat{g}_\rho(\hat{x}^k) + v^k$. Therefore, we can rewrite (A.9) as

$$\partial \psi(\hat{x}^{k+1}) = \rho^{-1}(v^k + \hat{g}_\rho(\hat{x}^k) + \hat{x}^{k+1} - \hat{x}^k) + \partial \mathcal{I}_\mathcal{X}(\hat{x}^{k+1}).$$

From [Lemma 4](#) we have $0 \in \rho^{-1}(\hat{g}_\rho(\hat{x}^k) + \hat{x}^{k+1} - \hat{x}^k) + \partial \mathcal{I}_\mathcal{X}(\hat{x}^{k+1})$, thus $\rho^{-1}v^k \in \partial \psi(\hat{x}^{k+1})$. This allows us to rewrite (A.8) as

$$\psi(y) - f(\hat{x}^{k+1}) \geq \langle Lv^k, y - \hat{x}^{k+1} \rangle + \frac{1}{2\rho} \|y - \hat{x}^{k+1}\|^2,$$

$\forall \hat{x}^{k+1} \in \mathcal{X}_{(p,q)}$, for some $v^k \in \mathcal{B}_\Omega^n$. Undoing the expression of $\psi(y)$ and particularizing to $y = x^* \in \mathcal{X}$ leads to

$$\begin{aligned} f(\hat{x}^*) - f(\hat{x}^{k+1}) &\geq \frac{1}{2\rho} \|\gamma^{k+1}\|^2 - \frac{1}{2\rho} \|\gamma^k\|^2 + f(\hat{x}^*) - f(\hat{x}^k) \\ &\quad - \langle \nabla f(\hat{x}^k), \hat{x}^* - \hat{x}^k \rangle + \rho^{-1} \langle v^k, \hat{x}^* - \hat{x}^{k+1} \rangle. \end{aligned}$$

Since f is a σ -strongly convex function, we have that ([Beck, 2017](#), Theorem 5.24.(ii))

$$f(\hat{x}^*) - f(\hat{x}^k) - \langle \nabla f(\hat{x}^k), \hat{x}^* - \hat{x}^k \rangle \geq \frac{\sigma}{2} \|\hat{x}^* - \hat{x}^k\|^2.$$

Thus,

$$f(\hat{x}^*) - f(\hat{x}^{k+1}) \geq \frac{1}{2\rho} \|\gamma^{k+1}\|^2 - \frac{\rho^{-1} - \sigma}{2} \|\gamma^k\|^2 - \rho^{-1} \langle v^k, \gamma^{k+1} \rangle. \quad (A.10)$$

By definition of $\hat{x}^*$, we have that $f(\hat{x}^*) - f(\hat{x}^{k+1}) \leq 0$. Therefore, the right hand side of (A.10) must also be less or equal to 0, which leads to

$$\begin{aligned} \frac{1}{2} \|\hat{x}^{k+1} - \hat{x}^*\|^2 &\leq \frac{1 - \rho\sigma}{2} \|\hat{x}^k - \hat{x}^*\|^2 + \langle v^k, \hat{x}^{k+1} - \hat{x}^* \rangle \\ &\stackrel{(*)}{\leq} \frac{1 - \rho\sigma}{2} \|\hat{x}^k - \hat{x}^*\|^2 + \|v^k\| \cdot \|\hat{x}^{k+1} - \hat{x}^*\| \\ &\stackrel{(**)}{\leq} \frac{1 - \rho\sigma}{2} \|\hat{x}^k - \hat{x}^*\|^2 + 2\Omega\epsilon^{-1} \|\hat{x}^{k+1} - \hat{x}^*\|^2, \end{aligned}$$

where in (*) we are making use of the Cauchy-Schwarz inequality and in (**) of the fact that $\|v^k\| \leq \Omega$ and $\|\hat{x}^{k+1} - \hat{x}^*\| > \frac{\epsilon}{2}$. Since by construction $\rho\sigma \leq 1$, the assumption $4\Omega\epsilon^{-1} < \rho\sigma$ implies $2\Omega\epsilon^{-1} < \frac{1}{2}$. Thus, we derive

$$\|\hat{x}^{k+1} - \hat{x}^*\|^2 \leq \left(\frac{1 - \rho\sigma}{1 - 4\Omega\epsilon^{-1}} \right) \|\hat{x}^k - \hat{x}^*\|^2,$$

which leads to claim (i) if applied recursively, where we note that the assumption $4\Omega\epsilon^{-1} < \rho\sigma$ guarantees that the sequence is convergent.

We now prove claim (ii) by rearranging (A.10) and proceeding as follows:

$$\begin{aligned} f(\hat{x}^{k+1}) - f(\hat{x}^*) &\leq \frac{\rho^{-1} - \sigma}{2} \|\gamma^k\|^2 - \frac{1}{2\rho} \|\gamma^{k+1}\|^2 + \rho^{-1} \langle v^k, \gamma^{k+1} \rangle \\ &\leq \frac{\rho^{-1} - \sigma}{2} \|\gamma^k\|^2 - \frac{1}{2\rho} \|\gamma^{k+1}\|^2 + 2\rho^{-1} \Omega\epsilon^{-1} \|\gamma^{k+1}\|^2 \\ &\leq \frac{\rho^{-1} - \sigma}{2} \|\gamma^k\|^2 + \rho^{-1} \left(2\Omega\epsilon^{-1} - \frac{1}{2} \right) \|\gamma^{k+1}\|^2 \\ &\stackrel{(*)}{\leq} \frac{1 - \rho\sigma}{2\rho} \|\gamma^k\|^2 = \frac{1 - 4\Omega\epsilon^{-1}}{2\rho} \left(\frac{1 - \rho\sigma}{1 - 4\Omega\epsilon^{-1}} \right) \|\gamma^k\|^2 \\ &\stackrel{(**)}{\leq} \frac{1 - 4\Omega\epsilon^{-1}}{2\rho} \left(\frac{1 - \rho\sigma}{1 - 4\Omega\epsilon^{-1}} \right)^{k+1} \|\hat{x}^0 - \hat{x}^*\|^2, \end{aligned}$$

$\forall \hat{x}^{k+1} \in \mathcal{X}_{(p,q)}, \forall k \geq 0$, where $(*)$ holds since $2\Omega\epsilon^{-1} < \frac{1}{2}$ and $(**)$ follows from claim (i). ■

References

- Ahmed, D., Peruffo, A., & Abate, A. (2020). Automated and sound synthesis of Lyapunov functions with SMT solvers. In A. Biere, & D. Parker (Eds.), *Lecture notes in computer science: vol. 12078, Tools and algorithms for the construction and analysis of systems (TACAS 2020)* (pp. 97–114). Cham: Springer.
- Alamo, T., Krupa, P., & Limon, D. (2019). Restart FISTA with global linear convergence. In *18th European control conference (ECC)* (pp. 1969–1974). IEEE.
- Beck, A. (2017). *MOS-SIAM series on optimization, First-order methods in optimization*. SIAM – Society for Industrial and Applied Mathematics.
- Bemporad, A. (2021). Explicit model predictive control. In J. Baillieul, & T. Samad (Eds.), *Encyclopedia of systems and control* (pp. 744–751). Cham: Springer International Publishing.
- Bertsekas, D. P. (2009). *Convex optimization theory*. Belmont, Massachusetts: Athena Scientific.
- Clarke, E., Kroening, D., & Lerda, F. (2004). A tool for checking ANSI-C programs. In K. Jensen, & A. Podolski (Eds.), *Lecture notes in computer science: vol. 2988, Tools and algorithms for the construction and analysis of systems (TACAS 2004)* (pp. 168–176). Berlin, Heidelberg: Springer.
- Cohen, P., Feron, E., & Garoche, P.-L. (2020). Verification and validation of convex optimization algorithms for model predictive control. *Journal of Aerospace Information Systems*, 17(5), 257–270.
- Devolder, O., Glineur, F., & Nesterov, Y. (2014). First-order methods of smooth convex optimization with inexact oracle. *Mathematical Programming*, 146(1), 37–75.
- Eén, N., & Sörensson, N. (2004). An extensible SAT-solver. In E. Giunchiglia, & A. Tacchella (Eds.), *Lecture notes in computer science: vol. 2919, Theory and applications of satisfiability testing* (pp. 502–518). Berlin, Heidelberg: Springer.
- Fang, C., Rutenbar, R., & Tsuhan Chen (2003). Fast, accurate static analysis for fixed-point finite-precision effects in DSP designs. In *International conference on computer aided design* (pp. 275–282). IEEE.
- Frison, G., & Diehl, M. (2020). HPIPM: a high-performance quadratic programming framework for model predictive control. *IFAC-PapersOnLine*, 53(2), 6563–6569.
- Garone, E., Di Cairano, S., & Kolmanovsky, I. (2017). Reference and command governors for systems with constraints: A survey on theory and applications. *Automatica*, 75, 306–328.
- Jerez, J. L., Kerrigan, E. C., & Constantinides, G. A. (2011). A condensed and sparse QP formulation for predictive control. In *IEEE conference on decision and control and european control conference* (pp. 5217–5222). IEEE.
- Krupa, P., Jaouani, R., Limon, D., & Alamo, T. (2021). A sparse ADMM-based solver for linear MPC subject to terminal quadratic constraint. *arXiv:2105.08419*.
- Krupa, P., Limon, D., & Alamo, T. (2021). Implementation of model predictive control in programmable logic controllers. *IEEE Transactions on Control Systems Technology*, 29(3), 1117–1130.
- Nadales, J. M., Manzano, J. M., Barriga, A., & Limon, D. (2022). Efficient FPGA parallelization of Lipschitz interpolation for real-time decision-making. *IEEE Transactions on Control Systems Technology*, 30(5), 2163–2175.
- Nesterov, Y. (2013). Gradient methods for minimizing composite functions. *Mathematical Programming*, 140(1), 125–161.
- Parikh, N., & Boyd, S. (2013). Proximal algorithms. *Foundations and Trends in Optimization*, 1(3), 123–231.
- Patrinos, P., Guiggiani, A., & Bemporad, A. (2015). A dual gradient-projection algorithm for model predictive control in fixed-point arithmetic. *Automatica*, 55, 226–235.
- Rawlings, J. B., Mayne, D. Q., & Diehl, M. (2017). *Model predictive control: theory, computation, and design* (2nd ed.). Madison, Wisconsin: Nob Hill Publishing.
- Richter, S. (2012). *Computational complexity certification of gradient methods for real-time model predictive control* (Ph.D. thesis), ETH Zurich.
- Ryu, E. K., & Boyd, S. (2016). A primer on monotone operator methods. *Applied and Computational Mathematics*, 15(1), 3–43.
- Saracco, P., Batic, M., Hoff, G., & Pia, M. G. (2012). Uncertainty quantification (UQ) in generic MonteCarlo simulations. In *IEEE nuclear science symposium and medical imaging conference record (NSS/MIC)* (pp. 651–656). IEEE.
- Simić, S., Bemporad, A., Inverso, O., & Tribastone, M. (2022). Tight error analysis in fixed-point arithmetic. *Formal Aspects of Computing*, 34(1), 1–32.
- Stellato, B., Banjac, G., Goulart, P., Bemporad, A., & Boyd, S. (2020). OSQP: An operator splitting solver for quadratic programs. *Mathematical Programming Computation*, 12(4), 637–672.
- Vakili, S., Langlois, J. M. P., & Bois, G. (2013). Finite-precision error modeling using affine arithmetic. In *IEEE international conference on acoustics, speech and signal processing* (pp. 2591–2595). IEEE.



Pablo Krupa received his Master's degree in Industrial Engineering in 2017 and his Ph.D. in Systems Engineering and Automation in 2021 from the University of Seville, Spain. In 2017/18 he was with the Mitsubishi Electric Research Laboratories, Cambridge, USA, where he worked on the development and implementation of model predictive controllers for building heat and ventilation systems. Since 2022, he is a postdoctoral visiting researcher at IMT School for Advanced Studies, Lucca, Italy, working on various topics related to model predictive control and optimization algorithms.

His current research interests include model predictive control, robust control, convex optimization and certification of optimization algorithms.



Omar Inverso received his Master's degree in Computer Science in 2009 from the University of Salerno, Italy, and his Ph.D. in Computer Science in 2015 from the University of Southampton, England. In 2015 he also worked as a research fellow at the same university, and later joined the Gran Sasso Science Institute in L'Aquila as a postdoctoral researcher, where in 2017 he was appointed as an assistant professor. He is interested in programming languages, formal methods, concurrency, decision procedures, software verification, and in particular in tailored implementations for automated and efficient analysis of specific software systems.

He co-authored several papers on different topics, including efficient and parallel bug-finding in multi-threaded programs, specification and verification of distributed systems, seamless integration of non-integer arithmetic semantics into existing program verification flows. He is the developer of CSeq, a framework for quick prototyping of static analyzers and program verifiers for the C language, and different tools developed within that framework, including a prototype for bit-precise analysis of control software under non-integer arithmetic based on bounded model checking, and an award-winning tool for multi-threaded programs (Lazy-CSeq). He also worked on a tool for domain-specific languages (Sliver), that verifies safety and liveness of systems specified in arbitrary domain-specific languages via off-the-shelf verification tools for C, and on Erlang encodings (AErlang) for a domain-specific language for concurrent systems.



Mirco Tribastone is Full Professor of Computer Science at IMT School for Advanced Studies Lucca since 2020, where he leads the research group SysMA - Systems Security Modeling and Analysis. Previously, he has been Associate Professor of Computer Science at IMT since 2015, after holding a position as Associate Professor at the University of Southampton (2013–2015) and as Juniorprofessor at the Ludwig-Maximilians University of Munich (2010–2013). He received a Ph.D. in Computer Science from the University of Edinburgh in 2010. Mirco's research interests are related to the

development and analysis of models for dynamical systems, with a focus on the study of performance for computer systems and applications to complex networks.



Alberto Bemporad received his Master's degree cum laude in Electrical Engineering in 1993 and his Ph.D. in Control Engineering in 1997 from the University of Florence, Italy. In 1996/97 he was with the Center for Robotics and Automation, Department of Systems Science & Mathematics, Washington University, St. Louis. In 1997–1999 he held a postdoctoral position at the Automatic Control Laboratory, ETH Zurich, Switzerland, where he collaborated as a Senior Researcher until 2002. In 1999–2009 he was with the Department of Information Engineering of the University of Siena, Italy, becoming an Associate Professor in 2005. In 2010–2011 he was with

the Department of Mechanical and Structural Engineering of the University of Trento, Italy. Since 2011 he has been a Full Professor at the IMT School for Advanced Studies Lucca, Italy, where he served as the Director of the institute in 2012–2015. He spent visiting periods at Stanford University, University of Michigan, and Zhejiang University. In 2011 he co-founded ODYS S.r.l., a company specialized in developing model predictive control systems for industrial production. He has published more than 400 papers in the areas of model predictive control, hybrid systems, optimization, automotive control, and is the co-inventor of 21 patents. He is the author or coauthor of various software packages for model predictive control design and implementation, including the Model Predictive Control Toolbox (The Mathworks, Inc.) and the Hybrid Toolbox for MATLAB. He was an Associate Editor of the IEEE Transactions on Automatic Control during 2001–2004 and Chair of the Technical Committee on Hybrid Systems of the IEEE Control Systems Society in 2002–2010. He received the IFAC High-Impact Paper Award for the 2011–14 triennial, the IEEE CSS Transition to Practice Award in 2019, and the 2021 SAE Environmental Excellence in Transportation Award. He has been an IEEE Fellow since 2010.